

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: **RMPP141, RMPP394 Grey, RLPP721**

Intended Use: Raw material for plastic industry.

Manufacturer: Salee Colour Public Co., Ltd
858 Moo 2, Soi 1C/1, Bangpu Industrial Estate,
Bangpumai, Muang Samutprakarn,
Samutprakarn 10280, Thailand
Ph: +66 2 323 2601 to 08
Fax: +66 2 323 2227 to 8
<http://www.saleecolour.com>

2. HAZARDS

The product is not classified as hazardous.

Inhalation of dust may irritate the respiratory tract. Spilled pellets or powder may be a slipping hazard.

3. COMPOSITION

This product is a polypropylene, ethylene copolymer. Contains no substance classified as hazardous. The product range includes polypropylene with UV, Anti-oxidant and compatibiliser.

4. FIRST AID MEASURES

Swallowed:

Not probable. Seek medical advice

Eye:

Flush with plenty of water for at least 15 minutes. Seek medical attention.

Skin:

Molten plastic causes severe thermal burns. Cool rapidly with water and seek medical attention. Do not pull off the skin.

In case of contact with condensed processing fumes, immediately flush the area with plenty of water. Remove contaminated clothing before reuse. Get medical attention if irritation persists.

MATERIAL SAFETY DATA SHEET

Inhaled:

If fumes are inhaled, remove person to fresh air. If breathing difficult get medical attention.

First Aid Facilities:

Provide eye baths and safety showers close to areas where there is significant potential for eye and skin contact.

5. FIRE FIGHTING MEASURES

Use water, foam or dry chemicals to extinguish the fire. Product will burn under fire conditions,

Firefighters and others who may be exposed to products of combustion should wear self-contained breathing apparatus. Equipment should be thoroughly decontaminated after use.

Hazardous Decomposition Products:

There are no significant decomposition products occurring in the product below about 230°C (447°F). Decomposition product at greater than about 300°C (570°F) is principally carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES.

No flames, No sparks. Eliminate all sources of ignition. In case of spill suck or sweep up material to prevent slipping accidents.

Heating and processing the product above 300°C (570°F) should be avoided. Overheating the plastic may occur due to excessively-high cylinder heats, overworking of the melt by wrong screw configuration, or by long dwell time in the machine. Under such conditions the thermal emissions and heat-degradation products might, without proper ventilation, reach hazardous concentrations in the converting area (see “Hazardous Decomposition Products” section).

7. HANDLING AND STORAGE

During processing small amounts of volatile hydrocarbons may be released. Provide adequate ventilation and avoid breathing these fumes.

The product should be stored in dry conditions at temperatures less than 50°C (120°F).

MATERIAL SAFETY DATA SHEET

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Respiratory Protection: Not ordinarily required

Protective Clothing: Not ordinarily required

Inhalable dust 10 mg/m³ max

Keep exposures as low as practicable below exposure standards.

Provide mechanical ventilation to control exposure levels below airborne exposure standards and to prevent operator discomfort. In general, ventilation should be provided at compounding and converting areas and at fabricating work stations which involve heating the plastic. Local exhaust hoods may be used over die-heads of extrusion equipment or in the vicinity of thermoforming and moulding machines, where practicable.

Respiratory Protection:

Avoid breathing dust, processing fumes and/or vapours. Use approved respiratory protection equipment when airborne exposure standards are exceeded or where operator discomfort is experienced.

Eye:

Safety glasses with side shields are recommended to avoid eye contact.

Skin Protection:

The product presents no skin concern requiring special protection except as noted under "Other precautions".

Other Precautions:

The greatest potential for injury occurs when working with the molten material such as during purging of the moulding machine, extruder and the like. During this type of operation it is essential that all workers in the immediate area wear eye and skin protection (e.g. full face shield and safety glasses, heat resistant gloves, overalls and safety boots) as protection from thermal burns.

Fumes or vapours emitted from the hot melted plastic during converting operations may condense on cool overhead metal surfaces or exhaust ducts. That condensate, usually in the form of a soft grease like semi-solid, may contain substances which are irritating or toxic. Avoid contact of that material with the skin. Wear rubber or other impermeable protective gloves when cleaning contaminated areas.

MATERIAL SAFETY DATA SHEET

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Description/Properties	
Appearance	Pellet /Powder
Boiling Point:	Not applicable
Melting Point:	160 – 170°C (320°F – 338°F)
Vapour Pressure:	Not applicable
Specific Gravity:	0.89
Flash Point:	>316°C (>600°F)
Flammability Limits:	Not applicable
Solubility in Water:	Insoluble

Other Properties	
Odour:	Odourless
Softening Point:	103 – 128°C Method: ASTM 1525
Flash Ignition Temperature:	N/A Method: ASTM-1929(B)
Auto Ignition Temperature:	N/A Method: ASTM-1929(B)
Percent Volatiles	Less than 1%

10. STABILITY AND REACTIVITY

The product is a stable thermoplastic. There is no chemical reactivity. On combustion, fumes containing oxides of carbon will be released.

11. TOXICOLOGICAL INFORMATION.

Chronic:

This product (or component) is not listed in IARC Monographs, the NTP Sixth Annual Report or the ACGIH TLVs as a carcinogen or potential carcinogen. It is not regulated by OSHA as a carcinogen.

12. ECOLOGICAL INFORMATION

The product is not classified as being hazardous to the environment.

MATERIAL SAFETY DATA SHEET

13. DISPOSAL

Spillages on hard surfaces present a slip hazard. Sweep or vacuum up promptly.

The granules may cause sewer and waterway obstruction; fish may eat pellets and obstruct their digestive tracts. Prevent exit to sewer and waterways. Remove sources of ignition. Collect material into containers.

Recycle, incinerate or landfill as per local, state and federal regulations.

14. TRANSPORT

Not classified as a Dangerous Good (see “Identification” section). Store in a cool dry area.

15. REGULATORY INFORMATION

Not applicable

16. OTHER INFORMATION

The information contained herein is based on current knowledge, documents and data available; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider this data only as a supplement to other information. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment.

Important: *The information contained in this document is of a general nature only and is intended to provide an indication of the potential properties and benefits of a particular polypropylene compound. The statistical and other information provided in this document has been determined in laboratory test conditions. Accordingly, there may be differences in performance in a production environment including having regard to the materials used. The information contained in this document should not be used as a sole basis for production or manufacturing purposes. Independent testing verification and independent professional advice should be obtained before making a decision to use any product or to apply any method or process. To the full extent permitted by law, Salee Colour Public Company Limited (Salee Colour) its related entities, their directors /employees: & sales company PSD Rotoworx P/L, (i) give no warranty or representation that the information contained in this document is accurate and complete in every particular, and (ii) disclaim all liability for reliance on the information contained in this document.*

**Salee Colour Public Company Limited,
858 Moo 2, Soi 1C/1,
Bangpu Industrial Estate,
Bangpumai, Muang Samutprakarn
Samutprakarn 10280, Thailand
Contact: sales@psdrotoworx.com**